

LISTING OF CLAIMS

1-2. (canceled)

3. (currently amended) A proxy server for relaying communications between applications and for performing an additional process comprising:

a key manager for managing multiple keys used to generate a digital signature to be provided for a message document that is exchanged between said applications, wherein each of said multiple keys is used to sign messages having particular message contents;

a signature key determiner for extracting said message document from a predetermined application, and for, based on the contents of said message document, determining a key from said multiple keys that is to be used to provide a digital signature, wherein said contents do not include any digital signature data; and

a signature generator for providing a digital signature for said message document by using said key that is obtained from said key manager based on a determination made by said signature key determiner, and for transmitting said message document with said digital signature to a destination application ~~The proxy server according to claim 2,~~

wherein said key manager sets multiple key selection rules for obtaining said key, and only when said key selection rules are satisfied can said signature generator obtain said key, and wherein, when said key for generating a digital signature for said message document can not be obtained, said signature generator employs a replacement key that is defined in advance to provide a digital signature.

JP920000300US1

-2-

4. (original) A proxy server according to claim 3, wherein, after said signature generator has provided a digital signature using said replacement key, when said acquisition condition that is determined for the original key based on said message document is satisfied to enable the acquisition of said original key, said signature generator again provides a digital signature using said original key.

5. (canceled)

6. (currently amended) The proxy server according to claim 4, further comprising a log manager for storing said message document with a digital signature provided by said signature generator, and for managing a log, and wherein said log manager stores not only said message document for which said signature generator has provided a digital signature using said replacement key, but also said message document without digital signature; and wherein said signature generator obtains, from said log manager, said message document without said digital signature, and provides a digital signature using said original key.

7-8. (canceled)

9. (currently amended) A digital signature system comprising:
applications for performing data processing; and
a proxy server connected to said applications via a network,

JP920000300US1

-3-

wherein said proxy server manages multiple keys, wherein each of said multiple keys is used to sign messages having particular message contents, and wherein said proxy server intercepts a communication, transmitted through said network, from one of said applications to an external destination device, selects one of said multiple keys based on said message contents, provides a digital signature for a message document exchanged via said communication using said key selected based on the contents of said message document, wherein said contents do not include any digital signature data, and transmits said message document with said digital signature to said external destination device, and

wherein said proxy server permits a key used to provide a digital signature to be changed in accordance with the contents of a message document; and wherein said proxy server sets key selection rules for said key and permits digital signature using said key when said key selection rules have been satisfied, and ~~The digital signature system according to claim 8,~~ wherein, when said key selection rules for said key used to provide a digital signature for said message document have not been satisfied, said proxy server employs a predetermined replacement key to provide a digital signature; and wherein, when said key selection rules for said key are satisfied after said digital signature has been provided using said replacement key, said proxy server again employs said key to provide a digital signature for said message document.

10-17. (canceled)

JP920000300US1

-4-

18. (previously presented) A storage medium on which input means of a computer stores a computer-readable program that permits said computer to perform:

a process for selecting one of a plurality of keys used to provide a digital signature for a message document in accordance with the contents of message document transmitted from a predetermined application, wherein said contents do not include any digital signature data and wherein each of said plurality of keys is used to sign messages having particular message contents;

a process for providing a digital signature for said message document using said key that is selected, and for employing a predetermined replacement key to provide said digital signature for said message document, when key selection rules for said key used to provide a digital signature for said message document have not been satisfied; and

a process for employing said key to provide again a digital signature for said message document, when said key selection rules for said key are satisfied after said digital signature has been provided using said replacement key.

19. (canceled)

20. (previously presented) A program transmission apparatus comprising:

storage means for storing a program that permits a computer to perform:

JP920000300US1

-5-

a process for selecting one of multiple keys used to provide a digital signature for a message document in accordance with the contents of the message document transmitted from a predetermined application, wherein said contents do not include any digital signature data and wherein each of said multiple keys is used to sign messages having particular message contents;

a process for providing a digital signature for said message document using said key that is selected, and for employing a predetermined replacement key to provide said digital signature for said message document when key selection rules for said key used to provide a digital signature for said message document have not been satisfied; and

a process for, when said key selection rules for said key are satisfied after said digital signature has been provided using said replacement key, employing said key to provide again a digital signature for said message document; and

transmission means for reading said program from said storage means, and for transmitting said program.

21-28. (canceled)

29. (currently amended) A computer-implemented digital signature method for providing a digital signature for a message document exchanged by applications and for authorizing said message document, comprising the steps of:

selecting, in accordance with the contents of a message document generated by one of said applications, one of a

JP920000300US1

-6-

plurality of keys used for providing a digital signature for said message document, wherein said contents do not include any digital signature data and wherein each of said plurality of is used to sign messages having particular message contents;

providing a digital signature for said message document; and

transmitting said message document with said digital signature to a destination designated by said one of said applications. ~~The digital signature method of claim 15~~ wherein key selection rules are provided for said key and further comprising the steps of:

providing a digital signature for said message document, when key selection rules set for said key are not established, by using a replacement key that is set in advance for said key;

using said key, when said key selection rules for said key have been satisfied after said digital signature has been provided using said replacement key, to again provide a digital signature; and

transmitting said message document with said digital signature to said destination.

JP920000300US1

-7-